



### Software

Specifications

Newly upgraded RIP software with higher functionali <mark>ty and mo</mark>	ore user-friendliness
Raster Link	PLUS
Added useful functions  ♦ [ID Cut] for consecutive cutting  ♦ [Multi layers print] for wider expressiveness	35000
<ul> <li>         ◆ Braille print for easy operation of braille print     </li> <li>         PDF including transparent effect is applicable.     </li> <li>         ◆ PDF data image with transparent effect is faithfully printable as the original.     </li> </ul>	

Item		CJV300-130 Plus	CJV300-160 Plus		
Printhead		On-demand piezo head (2 staggered printheads)			
Print resolution		360 dpi, 540 dpi, 720 dpi, 1080 dpi and 1440 dpi			
Maxir	num print width	1,361 mm (53.5 in) 1,610 mm (63.3 in)			
Maxir	mum media width	1,371 mm (53.9 in) 1,620 mm (63.7 in)			
Ink	Type/Color (*1)  Package size (*2)	Eco-solvent SS21 (C, M, Y, K. Lc, Lm, Lk, Or, W, Si) ES3 (C, M, Y, K, Lc, Lm, W) BS3 (C, M, Y, K) BS4 (C, M, Y, K) Water-based sublimation ink Sb54 (Bl, M, Y, K, Lbl, Lm)  SS21: 440ml Ink cartridge, 600ml/2L Ink pack (White&silver: 220ml ink cartridge only)			
	Circulation system	BS3/BS4: 600ml/2L Ink pack ES3: 440ml Ink cartridge (White: 220ml ink cartridge only) Sb54: 440ml Ink cartridge /2L Ink pack MCT (Mimaki Circulation Technology) only applies white and silver inks.			
Media	a thickness	1.0 mm or less			
	d media weight	45 kg (99.2 lb) or less			
Interf		USB 2.0/ Ethern	,		
	r supply	****	220-240V) x2 50Hz /60Hz ±1Hz		
	er consumption	1440W x 2 or less (AC100V) / 1920W x 2 or less (AC200V)			
Operational environment		Temperature: 20-30 °C (59-86 °F) Humidity: 35-65% Rh (Non condensing)			
Dime	nsions (W x D x H)	2,525 mm x 700 mm x 1,392 mm 2,775 mm x 700 mm x 1,392 m (99 in x 28 in x 55 in) (109 in x 28 in x 55 in)			
Weigl	ht	167 kg (370.4 lb)	178 kg (392.4 lb)		

## Print speed

4C (CMYK)							
PVC			Banner				
Print mode		Speed (m²/h)	Print mode		Speed (m²/h)		
Draft	540x720,4P	Bi	32.7	Super Draft	360x360,1P	Bi	105.9
High Speed	540x720.6P	Bi	24.6	Draft	540x360,2P	Bi	69.2
<u> </u>				High Speed	540x360,3P	Bi	45.0
Standard	720x1080,6P	Bi	20.2	Standard	540x720,4P	Bi	32.7
High Quality	720x1440,12P	Bi	10.4	High Quality	720x1080,6P	Bi	20.2

8C (CMYKLcLmLkOr) / 6C+W (CMYKLcLm+WW/WSi) (CMYKOrLk+WW/WSi)							
PVC			Banner				
Print mode		Speed (m²/h)	Print mode		Speed (m²/h)		
Draft	540x360,6P	Bi	22.7	Super Draft	360x360,2P	Bi	50.5
High Speed	540x720.8P	Bi	17.4	Draft	540x360,4P	Bi	33.9
				High Speed	540x360,6P	Bi	22.7
Standard	720x1080,12P	Bi	10.5	Standard	540x720,8P	Bi	17.4
High Quality	720x1440,24P	Bi	5.3	High Quality	720x1080,16P	Bi	7.9

The above print speed is by printed by CJV300-160 Plus.

## Supplies

Item	Color	Item No.	Remarks		
SS21	O IN A DAILY	SPC-0501x			
GREENGUARD Gold	C/M/Y/K Lc/Lm/Or/Lk	xColor	440ml Ink cartridge		
certifated ink	LO/LITI/OT/LK	C/M/Y/K/Lc/Lm/Or/Lk			
	Cyan	SS21-C-60			
	Magenta	SS21-M-60			
	Yellow	SS21-Y-60			
	Black	SS21-K-60	200 111		
	Light Cyan	SS21-LC-60	600ml Ink pack		
	Light Magenta	SS21-LC-60			
	Orange	SS21-OR-60			
	Light Black	SS21-LK-60			
	White	SPC-0504W-2			
	Silver	SPC-0504 Si	220ml Ink cartridge		
	Cyan	SPC-0588C			
	Magenta	SPC-0588M			
	Yellow	SPC-0588Y			
	Black				
		SPC-0588K	2L Ink pack		
	Light Cyan	SPC-0588LC			
	Light Magenta	SPC-0588LM			
	Orange	SPC-0588Or			
	Light Black	SPC-0588Lk			
ES3	Cyan	SPC-0440C			
	Magenta	SPC-0440M			
	Yellow	SPC-0440Y	440ml Ink cartridge		
	Black	SPC-0440K			
	Light Cyan	SPC-0440LC			
	Light Magenta	SPC-0440LM			
	White	SPC-0433W-2	220ml Ink cartridge		
BS3	Cyan	SPC-0667C			
	Magenta	SPC-0667M	600ml lnk nook		
	Yellow	SPC-0667Y	600ml Ink pack		
	Black	SPC-0667K			
	Cyan	SPC-0693C			
	Magenta	SPC-0693M	Ol Jalonado		
	Yellow	SPC-0693Y	2L Ink pack		
	Black	SPC-0693K			
BS4	Cyan	BS4-C-60			
	Magenta	BS4-M-60			
	Yellow	BS4-Y-60	600ml Ink pack		
	Black	BS4-K-60			
	Cyan	BS4-C-2L			
	Magenta	BS4-M-2L			
	Yellow	BS4-Y-2L	2L Ink pack		
	Black	BS4-K-2L			
Sb54					
ECO PASSPORT	Blue	SB54-BLT-44			
certifated ink	Magenta	SB54-MT-44			
- I matos mit	Yellow	SB54-YT-44	440ml Ink cartridge		
	Black	SB54-KT-44			
	Light Blue	SB54-LBT-44			
	Light Magenta	SB54-LMT-44			
	Blue	SB54-BLT-2L			
	Magenta	SB54-MT-2L			
	Yellow	SB54-YT-2L	2L Ink pack		
	Black	SB54-KT-2L	ZE IIIN PAON		
	Light Blue	SB54-LBT-2L			
	Light Magenta	SB54-LMT-2L			
MS Cleaning		SPC-0294	220ml Ink cartridge		
Washing		SPC-0259	220ml Ink cartridge		
	tridge	OPT-J0361	4 c/s		

Some of the samples in this catalog are artificial renderings. Specifications, design and dimensions stated in this catalog may be subject to change without notice (for technical improvements etc). corporate names and merchandise names written in this catalog are the trademark or registered trademark of the respective corporations. Inkjet printers print using extremely fine dots, so colors may very slightly vary after replacement of the printing heads. Also note that if using multiple printer units, colors could vary slightly from one unit to other units due to slight individual differences. Please note that descriptions and data in this catalog are as of October 2019.



## MIMAKI ENGINEERING CO., LTD.

2182-3 Shigeno-otsu, Tomi-city, Nagano 389-0512, Japan

## Mimaki Global Network

MIMAKI USA, INC.

MIMAKI BRASIL COMERCIO E IMPORTAÇÃO LTDA MIMAKI INDIA PRIVATE LIMITED Taiwan MIMAKI ENGINEERING (TAIWAN) CO.,LTD.

Singapore MIMAKI SINGAPORE PTE. LTD.

Europe MIMAKI EUROPE B.V. Indonesia PT. MIMAKI INDONESIA Australia MIMAKI AUSTRALIA PTY. LTD. China SHANGHAI MIMAKI TRADING CO.,LTD. Thailand MIMAKI (THAILAND) CO.,LTD.

## Contact us for details

DB10352-01



For

SIGN

**GRAPHICS** 

**Print & Cut Inkjet Printer** equipped with silver ink



# CJV300PIusseries CJV300-130/160Plus









<sup>\*1:</sup> BS3/BS4 are available in specific countries.
\*2: Optional Mimaki Bukl Ink System (MBIS3) is required for using 2L ink pack.
GREENGUARD Gold: Applicable products to this "GREENGUARD Gold certification" are acceptable environments such as schools and medical facilities based on the most strict global standard of chen

# CJV300-130/160Plus

High-performance inkjet printer equipped with eco-solvent ink, which is a print & cut printer wherein environmental protection is achieved by means of additional ecology & economy as well as by work efficiency

> Labor-saving & Efficiency

3 Plus

High image quality Stability

Ecology

Economy



## Labor-saving process & **Business efficiency are additional features**

# Adoption of ID Cut!


- With this single unit, work efficiency of Print & Cut can be improved -

What is ID Cut?

When the printing operation is performed using CJV300-130/160 Plus and RL6 Plus, ID that has recorded cutting information as well as material rotation information is printed out simultaneously. When the register mark sensor reads such ID, it asks the applicable PC to send cutting data information to it, and starts the cutting operation automatically. Since ID is printed out in four directions, a correct cutting operation will be performed because the machine recognizes an orientation of any


It eliminates the need for any operator to give cutting instruction to each data from RIP software unlike before while it makes it possible to do cutting operation, and prevents media loss due to data transmission mistake.

media, regardless of orientation of such



## In the past...

Any operators scanned register marks and specified cut data after each cutting job was completed



## ID Cut function of CJV300-130/160 Plus

This single unit of printer alone enables labels,

stickers, car lapping films or the like to be created.

In the ID Cut function, even if there are a large number of types of cut data, any operator performs manual operation only once at first!

# Ethernet supported!

- Support for Ethernet connection implements free and efficient work environment -

To the conventional connection method to PC for RIP, Ethernet connection has newly been added.

Unlike the conventional USB connection, connection via Ethernet can be established via network cable, and thus connection to a printer from any PC within network is now available. More free and efficient work-site environment can be put in place, by editing data using any PC in your office, then sending print data directly to a printer in your work operation site, for example.



# **Ecology & Economy are newly added features**

# Adoption of Eco-cartridge

A new Mimaki Eco-cartridge(\*) has been adopted with a replaceable 600ml ink pack. The Eco-cartridge is a reusable plastic case with a 600ml ink pack that can be replaced by customers. Using the Eco-cartridge will reduce the disposal of plastic 440ml cartridge every time ink is replaced, leading to environmental protection. In addition, the increased ink capacity reduces the need for cartridge replacement and add labor-saving process & business efficiency. The 8 colors (C, M, Y, K, Lc, Lm, Lk, Or) of SS21 600ml ink pack are newly prepared for the Eco-cartridge application.




(\*) The Mimaki Eco-cartridge is only compatible with 600ml ink packs.



# Newly added functions to support higher image quality and stability

## MAPS4

In ordinary textile printers, the straight pass boundaries often results in bandings and discoloration due to slight misalignment. The "MAPS4 (Mimaki Advanced Pass System 4)" functionality provides gradation to printed pass boundaries and reduces banding and uneven color, achieving a beautiful printing result.



Banding occurs at pass boundaries. Image quality is damaged seriously because horizontal streaks Printing in gradation



Because printing pass boundaries are faded in gradation, a beautiful image quality is ensured by

# Adoption of newly designed feeding & winding mechanism

- "End-face guide" for maximum loadable media in weight (45kg) comes equipped with as standard -


Through renewal of the older feeding & winding mechanism, stability of media conveyance has been improved, and thus the maximum loadable media weight has changed from 40kg to 45kg, making longer-sheet printout available. Also, it is provided with such an end-face guide as standard that prevents edge-surface meandering when any media are wound up, supporting high-quality printout through stable winding

## Our original and patented technology

# Mimaki's original 3-way intelligent heater

This 3-way intelligent heater fixes ink droplets placed on media in position. While temperature is controlled with Mimaki's original technology, heat is applied to media, and ink droplets are fixed in position with excellent color development and high-quality image being maintained. It achieves both stable color development and easy handling after output.

- Pre-heater: Heats media to optimum temperature before printing
- · Print heater: Dries ink droplets placed on media prior to ink bleeding, improving color
- Post-heater: Accelerates ink drying, realizing a stable winding
- · Top blower: Provides air blow to support ink drying



# Silver ink achieves impactful expression additionally!

SS21 silver ink can be used. As compared with a conventional silver ink, its brightness which is almost 1.67 times\* higher than that of it has been materialized. This makes it possible to provide brilliant and beautiful metallic expression.

\* Comparison with our conventional ES3 ink





Providing logo or background with silver color allows for impactful expression